

GENERAL PURPOSE TWIN CORE CABLES

AUDIO CABLES

Use
Transmission of Sound, Broadcast and Audio signals.

Insulation
V-90 HT PVC, Polyethylene or Polypropylene as indicated.

Sheath
Standard Grey V75 PVC, other materials or colours on request.

Screen
As indicated for each cable type below.

Conductor
Pack
100 or 500 meter reels.

Core Colour
Standard colours as indicated - other colour on request.

Note
These cables are not suitable for direct connection to mains supply.

UNSCREENED



Part Number	Nearest AWG	Cond. No. / Dia.	Insulation Type - Thickness mm	Core Colour	Sheath Type Dia.
HC2027	24	7/0.20 TC	PVC 0.25	BU + WW	PVC 3.50
HC2047	22	7/0.25 TC	PVC 0.38	RR + BK	PVC 4.95
HC2032	20	16/0.20 TC	PVC 0.30	RR + BK	PVC 4.95
HC2035	18	24/0.20 TC	PVC 0.45	RR + BK	PVC 5.10
HC2041	17	32/0.20 TC	PVC 0.45	RR + BK	PVC 6.75

TINNED COPPER WIRE BRAID SCREEN



Part Number	Nearest AWG	Cond. No. / Dia.	Insulation Type - Thickness mm	Core Colour	Sheath Type Dia.
HC2101	27	21/0.08 BC	PVC 0.20	RR + BK	PVC 3.05
HC2127	24	7/0.20 TC	PVC 0.25	BU + WW	PVC 3.50
HC2147	22	7/0.25 TC	PVC 0.38	RR + BK	PVC 4.95
HC2132	20	16/0.20 TC	PVC 0.45	RR + WW	PVC 5.10
HC2135	18	24/0.20 TC	PVC 0.45	RR + BK	PVC 5.70
HC2141	17	32/0.20 TC	PVC 0.45	RR + BK	PVC 7.00
HC2167	16	30/0.25 TC	PVC 0.45	RR + BK	PVC 7.20

Minimum order quantity will apply for some items.
 TC = Tinned Copper
 BC = Bare Copper

CMI Head Office NSW | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | nswsales@cmielectrical.com.au
CMI QLD-Brisbane
 (07) 3863 0749
 485A Zillmere Road,
 Zillmere QLD 4034
southqdsales@cmielectrical.com.au

CMI QLD - Rockhampton
 (07) 4921 0978
 Shop 3 at 76 Hollingsworth Street,
 North Rockhampton Qld 4701
northqdsales@cmielectrical.com.au

CMI VIC
 (03) 9532 1233
 3 Dissik Street,
 Cheltenham VIC 3192
vicsales@cmielectrical.com.au

CMI WA
 (08) 9358 1788
 36 Division Street,
 Welshpool WA 6106
wasaes@cmielectrical.com.au