

SPEAKER CABLES

AUDIO CABLES

Use
 Figure 8 - Speaker Cables.
Insulation
 V-75 PVC or V-90 HT PVC, as indicated.

Sheath
 As indicated below.

Screen
 As indicated below.

Conductor
 Bare Copper Wire

Pack
 100 or 500 meter reels.

Core Colour
 As indicated below.

Note
 These cables are not suitable for direct connection to mains supply. Minimum order quantity will apply for some items.

FIGURE 8 CONSTRUCTION - STANDARD - V-90 HT PVC (Black with White Stripe)



Part Number	Nom. Area Sq.	Cond. No. / Dia.	Insulation Type - Thickness mm	Nom. Sizes
HC3321	0.36	7/0.25 BC	PVC 0.50	3.80 x 1.80
HC3301	0.50	16/0.20 BC	PVC 0.40	3.80 x 1.80
HC3302	0.75	24/0.20 BC	PVC 0.90	3.9 x 1.9
HC3303	1.00	32/0.20 BC	PVC 0.80	6.35 x 3.1
HC3315	1.50	30/0.25 BC	PVC 0.80	7 x 3.00
HC3304	2.00	40/0.25 BC	PVC 0.80	7.1 x 3.4
HC3314	2.50	50/0.25 BC	PVC 1.00	8.6 x 4.2
HC3305	3.00	63/0.25 BC	PVC 1.00	8.80 x 4.30
HC3306	4.00	80/0.25 BC	PVC 1.00	9.40 x 4.60

100V INLINE DOUBLE INSULATED CABLE - V75 PVC (Black, Brown, White)



Part Number	Nom. Area Sq.	Cond. No. / Dia.	Insulation Type - Thickness mm	Nom. Sizes
HC2035 FLT	0.75	24/0.20 BC	0.45	5.20 x 3.20

FIGURE 8 CONSTRUCTION SUPER FLEX TYPE - V-90 HT PVC (Clear with white stripe)



Part Number	Nom. Area Sq.	Cond. No. / Dia.	Insulation Type - Thickness mm	Nom. Sizes
HC3317	1.50	85/0.15 BC	PVC 1.34	9.4 x 4.60
HC3319	2.00	113/0.15 BC	PVC 1.50	10.0 x 4.9
HC3318	3.00	169/0.15 BC	PVC 1.50	11.8 x 5.8
HC3323	4.00	226/0.15 BC	PVC 1.50	12.0 x 6.1

FIGURE 8 SCREENED STEREO CABLE - V-90 HT PVC / Al foil + Drain Wire / GREY V75 PVC Sheath)



Part Number	Nearest AWG	Core Colour	Cond. No./Dia. mm	Insulation Type - Thickness mm	Nom. Sizes
HCY076	24	Red/White + Black/Yellow	7/0.20 TC	PVC 0.25	3.5 x 7.2
HCY076 NSW	24	White/Green + Red/Black	7/0.20 TC	PVC 0.25	3.5 x 7.2

