

## SPEAKER CABLES

## AUDIO CABLES

**Use**  
 Figure 8 - Speaker Cables.  
**Insulation**  
 V-75 PVC or V-90 HT PVC, as indicated.

**Sheath**  
 As indicated below.

**Screen**  
 As indicated below.

**Conductor**  
 Bare Copper Wire

**Pack**  
 100 or 500 meter reels.

**Core Colour**  
 As indicated below.

**Note**  
 These cables are not suitable for direct connection to mains supply. Minimum order quantity will apply for some items.

FIGURE 8 CONSTRUCTION - STANDARD - V-90 HT PVC (Black with White Stripe)



Part Number	Nom. Area Sq.	Cond. No. / Dia.	Insulation Type - Thickness mm	Nom. Sizes
HC3321	0.36	7/0.25 BC	PVC 0.50	3.80 x 1.80
HC3301	0.50	16/0.20 BC	PVC 0.40	3.80 x 1.80
HC3302	0.75	24/0.20 BC	PVC 0.90	3.9 x 1.9
HC3303	1.00	32/0.20 BC	PVC 0.80	6.35 x 3.1
HC3315	1.50	30/0.25 BC	PVC 0.80	7 x 3.00
HC3304	2.00	40/0.25 BC	PVC 0.80	7.1 x 3.4
HC3314	2.50	50/0.25 BC	PVC 1.00	8.6 x 4.2
HC3305	3.00	63/0.25 BC	PVC 1.00	8.80 x 4.30
HC3306	4.00	80/0.25 BC	PVC 1.00	9.40 x 4.60

100V INLINE DOUBLE INSULATED CABLE - V75 PVC (Black, Brown, White)



Part Number	Nom. Area Sq.	Cond. No. / Dia.	Insulation Type - Thickness mm	Nom. Sizes
HC2035 FLT	0.75	24/0.20 BC	0.45	5.20 x 3.20

FIGURE 8 CONSTRUCTION SUPER FLEX TYPE - V-90 HT PVC (Clear with white stripe)



Part Number	Nom. Area Sq.	Cond. No. / Dia.	Insulation Type - Thickness mm	Nom. Sizes
HC3317	1.50	85/0.15 BC	PVC 1.34	9.4 x 4.60
HC3319	2.00	113/0.15 BC	PVC 1.50	10.0 x 4.9
HC3318	3.00	169/0.15 BC	PVC 1.50	11.8 x 5.8
HC3323	4.00	226/0.15 BC	PVC 1.50	12.0 x 6.1

FIGURE 8 SCREENED STEREO CABLE - V-90 HT PVC / Al foil + Drain Wire / GREY V75 PVC Sheath)



Part Number	Nearest AWG	Core Colour	Cond. No./Dia. mm	Insulation Type - Thickness mm	Nom. Sizes
HCY076	24	Red/White + Black/Yellow	7/0.20 TC	PVC 0.25	3.5 x 7.2
HCY076 NSW	24	White/Green + Red/Black	7/0.20 TC	PVC 0.25	3.5 x 7.2

