

SCREENED - PVC INSULATED CONNECTING WIRES

CONNECTING WIRES

Use
 Screen Flexible Wiring for Audio and other Electronic Equipment.

Pack
 100 or 500 meter reels

Insulation
 V-90 HT PVC or Polyethylene as indicated

Sheath
 Grey V75 PVC
 Other material and colour on request

Screen
 As indicated below for each cable type

Colour
 Dual Colour

Note
 These cables are not suitable for connection to mains supply.

Voltage
 The voltage rating given is generally in accordance with Defence specifications DEF 61-12(part 6) and DEF(Aust)8008.

TINNED COPPER WIRE BRAID SCREEN



Part Number	Nearest AWG	Cond. No./Dia. mm	Insulation Type - Thickness mm	Nom. Dia. mm	Max. Voltage
HC1101	27	21/0.08 BC	PVC 0.20	2.0	750
HC1128	24	7/0.20 TC	PVC 0.30	2.8	1000
HC1129	24	7/0.20 TC	PVC 0.45	3.3	1000
HC1132	20	16/0.20 TC	PVC 0.30	3.3	1000
HC1135	18	24/0.20 TC	PVC 0.45	4.1	1000

Minimum order quantities will apply for some items.

SPIRAL LAPPED TINNED COPPER SCREEN



Part Number	Nearest AWG	Cond. No./Dia. mm	Insulation Type - Thickness mm	Nom. Dia. mm	Max. Voltage
HC1201	27	21/0.08 BC	PVC 0.20	2.0	750
HC1512	25	14/0.12 TC	PE 0.38	2.8	1000
HC1229	24	7/0.20 TC	PVC 0.45	3.2	1000
HC1232	20	16/0.20 TC	PVC 0.30	3.2	1000
HC1235	20	24/0.20 TC	PVC 0.45	3.8	1000

Minimum order quantities will apply for some items.

TC = Tinned Copper
 BC = Bare Copper

CMI Head Office NSW | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | nswsales@cmielectrical.com.au
CMI QLD-Brisbane
 (07) 3863 0749
 485A Zillmere Road,
 Zillmere QLD 4034
southqldsales@cmielectrical.com.au

CMI QLD - Rockhampton
 (07) 4921 0978
 Shop 3 at 76 Hollingsworth Street,
 North Rockhampton Qld 4701
northqldsales@cmielectrical.com.au

CMI VIC
 (03) 9532 1233
 3 Dissik Street,
 Cheltenham VIC 3192
vicsales@cmielectrical.com.au

CMI WA
 (08) 9358 1788
 36 Division Street,
 Welshpool WA 6106
wasaless@cmielectrical.com.au