


Four Core + Earth Circular, 0.6/1kV Armoured X-90 XLPE

POWER CABLES

XLPE INSULATED PVC BEDDED STEEL WIRE ARMoured AND PVC SHEATHED CABLE TO AS/NZS 5000.1

CABLE APPLICATION

Description
 For mains, submains and subcircuits unenclosed in conduit, buried direct or in underground ducts for buildings and industrial plants where mechanical protection is required and where out of balance currents may require a neutral equal in size to the active. Suitable where space is at a premium and/or where conditions or overload may occur. Suitable for glanding.



CABLE DESIGN

Conductor
 Plain Annealed Copper Conductor to AS/NZS 1125
Insulation
 X-90 XLPE to AS/NZS 3808
 Core Colours: Red, White, Blue, Black, Green/Yellow
Sheath
 5V-90 PVC AS/NZS 3808
 Colours: Orange or Black (Black on request)

Note
 ** Items can be supplied with compacted conductors to AS/NZS 1125
 ** Items can be supplied with alternative stranding construction to AS/NZS 1125 – 7/19/37/61 strands
 ** overall dimensions may vary due to compacted conductors

CHARACTERISTICS

Part Number	Conductor				Cable				
	Nom. Area mm ²	No. & Dia. of Wires No./mm	Nom. Dia. mm	Nom. Insulation Thickness mm	Nom. Dia. Under Armour mm	Dia. of Wire mm	Nom. Dia. Over Armour mm	Nom. Overall Dia. mm	Approx. Mass Kg/100m
SOX7135C4CE	10	7/1.35	4.05	0.7	16.5	1.25	19.0	22.6	114.2
	E (4.0)	7/0.85	2.55						
SOX7170C4CE	16	7/1.70	5.1	0.8	18.7	1.6	21.9	25.5	159.0
	E (6.0)	7/1.04	3.12						
SOX19135C4CE	25	19/1.35**	6.75	0.9	22.2	1.6	25.4	29.0	214.1
	E (6.0)	7/1.04	3.12						
SOX19153C4CE	35	19/1.53**	7.65	0.9	25.0	1.6	28.2	32.0	267.9
	E (10)	7/1.35	4.05						
SOX19178C4CE	50	19/1.78**	8.9	1.0	28.6	2.0	32.6	36.6	370.0
	E (16)	7/1.70	5.1						
SOX19214C4CE	70	19/2.14**	9.8	1.1	33.1	2.0	37.1	41.5	489.5
	E (25)	19/1.35**	5.9						
SOX37178C4CE	95	37/1.78**	11.5	1.1	37.3	2.0	41.3	45.9	612.1
	E (25)	19/1.35**	5.9						
SOX37203C4CE	120	37/2.03**	13.1	1.2	41.9	2.5	46.9	51.9	782.2
	E (35)	19/1.35**	7.0						
SOX37225C4CE	150	37/2.25**	14.5	1.4	46.6	2.5	51.6	57.0	962.4
	E (50)	19/1.78**	8.2						
SOX37252C4CE	185	37/2.52**	16.2	1.6	52.4	2.5	57.4	63.0	1147.0
	E (70)	19/2.14**	9.8						
SOX61225C4CE	240	61/2.25**	18.6	1.7	58.6	2.5	63.6	69.6	1422.0
	E (95)	37/1.78**	11.5						

0.6/1kV XLPE SWA CIRCULAR

CMI Head Office NSW | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | nswsales@cmielectrical.com.au
CMI QLD-Brisbane
 (07) 3863 0749
 485A Zillmere Road,
 Zillmere QLD 4034
 southqdsales@cmielectrical.com.au

CMI QLD - Rockhampton
 (07) 4921 0978
 Shop 3 at 76 Hollingsworth Street,
 North Rockhampton Qld 4701
 northqdsales@cmielectrical.com.au

CMI VIC
 (03) 9532 1233
 3 Dissik Street,
 Cheltenham VIC 3192
 vicsales@cmielectrical.com.au

CMI WA
 (08) 9358 1788
 36 Division Street,
 Welshpool WA 6106
 wasales@cmielectrical.com.au