

## F-PM Series Blanking Plugs

For Explosion Protected Applications

Nickel plated brass blanking plugs are used to blank off unused entries for a permanent or temporary application.



Table 1

Part Number	Entry Thread Dia.	Across Corners	Across Flats	Max. Protrusion	Entry Thread Length	Sealing Washer	Locknut
F-PM16SS	M16x1.5	22.0	19.1	5.0	13.0	W16	PLN16
F-PM20	M20x1.5	27.0	22.4	6.0	13.0	W20	PLN20
F-PM25	M25x1.5	33.0	28.6	6.0	15.0	W25	PLN25
F-PM32	M32x1.5	40.4	37.3	8.0	21.0	W32	PLN32
F-PM40	M40x1.5	61.2	56.6	8.0	21.0	W40	PLN40
F-PM50	M50x1.5	73.9	68.3	10.0	21.0	W50	PLN50
F-PM63	M63x1.5	87.6	81.0	10.0	22.0	W63	PLN63
F-PM75	M75x1.5	99.7	92.1	12.0	24.0	W75	PLN75

## Fitting Instructions

Contact CMI Electrical for Fitting Instructions

## Certifications

Compliance: Explosion protected to IEC60079 Series  
 Protection: Ex db I/IC, Ex eb I/IC, Ex ta IIIC  
 Materials: Brass Nickel Plated  
 IP Rating: IP66/68 (7 Metres for 1 Hour)

**CMI Head Office NSW** | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | [nswsales@cmielectrical.com.au](mailto:nswsales@cmielectrical.com.au)  
**CMI QLD-Brisbane**  
 (07) 3863 0749  
 485A Zillmere Road,  
 Zillmere QLD 4034  
[southqldsales@cmielectrical.com.au](mailto:southqldsales@cmielectrical.com.au)

**CMI QLD - Rockhampton**  
 (07) 4921 0978  
 Shop 3 at 76 Hollingsworth Street,  
 North Rockhampton Qld 4701  
[northqldsales@cmielectrical.com.au](mailto:northqldsales@cmielectrical.com.au)

**CMI VIC**  
 (03) 9532 1233  
 3 Dissik Street,  
 Cheltenham VIC 3192  
[vic-sales@cmielectrical.com.au](mailto:vic-sales@cmielectrical.com.au)

**CMI WA**  
 (08) 9358 1788  
 36 Division Street,  
 Welshpool WA 6106  
[wasales@cmielectrical.com.au](mailto:wasales@cmielectrical.com.au)