


29 CORE TRAFFIC SIGNAL CABLE

STREET LIGHTING / TRAFFIC CONTROL CABLES

**PVC/PVC 29 CORE (26 x 1.5mm<sup>2</sup> + 3 x 2.5mm<sup>2</sup>) CABLE 0.6/1KV TO AS2276.1**

CABLE APPLICATION

**Description**  
Connection of Traffic Light Signal System.



CABLE DESIGN

**Conductor**  
Plain annealed Copper to AS/NZS 1125  
**Insulation**  
PVC V90 to AS/NZS 3808  
**Layup Construction**  
3 Cores - Grey, Black, Green/Yellow  
+ 10 Cores - White Core with Numbers (1-10)  
+ 16 Cores - White Core with Numbers (11-26)  
Diameter of Layup 21.5mm  
**Sheath**  
5V90 PVC to AS/NZS 3808 (Orange)  
**Certification**  
To Old Mains Roads requirement MRTS 256

CHARACTERISTICS

Part Number	Conductor			Insulation				Sheath		Conductor resistance (Max)		Weight
	No. of Core	Nom. Area mm <sup>2</sup>	No. & Dia. of Wires No./mm	Nom. Dia. mm	Nom. Insulation Thickness mm	Min. Nom. Ins. Thickness mm	Nom. Insulation Dia. mm	Nom. Sheath Thickness mm	Min. Dia. over Ins. mm	Overall Sheath Dia.	DC at 20°C Ohm/km	Approx. Cable Weight Kg/m
TFRCC29CTRAFFIC 3	2.5	7/0.67	2.0	1.0	0.62	3.6	1.8	1.43	25.3	7.41	4.8	
	26	1.5	7/0.50	1.5	0.8	0.62	3.1			13.6		

0.6/1kV, CU

**CMI Head Office NSW** | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | [nswsales@cmielectrical.com.au](mailto:nswsales@cmielectrical.com.au)  
**CMI QLD-Brisbane**  
(07) 3863 0749  
485A Zillmere Road,  
Zillmere QLD 4034  
[southqldsales@cmielectrical.com.au](mailto:southqldsales@cmielectrical.com.au)

**CMI QLD - Rockhampton**  
(07) 4921 0978  
Shop 3 at 76 Hollingsworth Street,  
North Rockhampton Qld 4701  
[northqldsales@cmielectrical.com.au](mailto:northqldsales@cmielectrical.com.au)

**CMI VIC**  
(03) 9532 1233  
3 Dissik Street,  
Cheltenham VIC 3192  
[vicsales@cmielectrical.com.au](mailto:vicsales@cmielectrical.com.au)

**CMI WA**  
(08) 9358 1788  
36 Division Street,  
Weshpool WA 6106  
[wasaless@cmielectrical.com.au](mailto:wasaless@cmielectrical.com.au)