


Multicore Flexible XLPE/PVC HD Cable 90°C 0.6/1kV

Highly Flexible
Heavy Duty
BC/XLPE/V90HT
V90HT PVC



Cable Construction

- Conductors:**
Annealed bare copper standard to AS/NZS 1125 class 5 & 6.
- Insulation:**
Special flexible XLPE compound comply to AS/NZS 3808.
- Protective sheath:**
Flame retardant NBR Elastomer for outstanding flexibility and durability in most hostile environments.
- Inner Sheath:**
Flexible V90HT PVC compound comply to AS/NZS 3808, Colour White.
- Outer Sheath:**
Flexible V90HT PVC compound comply to AS/NZS 3808, colour Orange or Black
- UV stabilised and flame retardant.

Temperature Range

-20 to +90°C

Rated Voltage

0.6/1kV

Relevant Standards

AS/NZS 1125, AS/NZS 3191, AS/NZS 5000.1, IEC 60332-1

Bending Radius

5 x diameter after installing
8 x diameter during installing

Typical Uses

In machine tools, construction and engineering equipment, conveyors and other industrial applications where outstanding flexibility is required under tough climatic and mechanical conditions. Diesel powered generator sets, load banks, ship to shore cables.

The materials used in the manufacture of these cables are RoHS Compliant.

Core Colour

2 core: Blue, Brown
3 core: Blue, Brown, Green/Yellow
4 core: Brown, Black, Grey, Green/Yellow
5 core: Blue, Red, White, Black, Green/Yellow
7 cores & above: White cores with numbered + Green/Yellow

Technical Data

Part Number	Nom. Stranding No./mm	Nom. Dia. mm	Nom. Insulation Thickness mm	Nom. Insulation Dia. mm	Layup Dia. mm	Nom. Inner Sheath Thickness mm	Nom. Inner Sheath Dia. mm	Nom. Outer Sheath Thickness mm	Nom. Overall Dia. mm
HDX03/1.0	32/0.20**	1.3	0.8	2.9	6.2	0.6	7.4	1.2	9.8
HDX04/1.0	32/0.20**	1.3	0.8	2.9	7.0	0.6	8.2	1.2	10.6
HDX05/1.0	32/0.20**	1.3	0.8	2.9	7.8	0.6	9.0	1.2	11.4
HDX02/1.5	48/0.20**	1.6	0.8	3.2	6.4	0.6	7.6	1.2	10.0
HDX03/1.5	48/0.20**	1.6	0.8	3.2	6.9	0.6	8.1	1.2	10.5
HDX04/1.5	48/0.20**	1.6	0.8	3.2	7.7	0.6	8.9	1.3	11.5
HDX05/1.5	48/0.20**	1.6	0.8	3.2	8.6	0.7	10.0	1.4	12.8
HDX07/1.5	48/0.20*	1.6	0.8	3.2	9.6	0.7	11.0	1.4	13.8
HDX12/1.5	48/0.20*	1.6	0.8	3.2	13.3	0.9	15.1	1.6	18.3
HDX02/2.5	80/0.20**	2.0	0.9	3.8	7.6	0.6	8.8	1.2	11.2
HDX03/2.5	80/0.20**	2.0	0.9	3.8	8.2	0.7	9.6	1.2	12.0
HDX04/2.5	80/0.20**	2.0	0.9	3.8	9.2	0.8	10.8	1.4	13.6
HDX05/2.5	80/0.20**	2.0	0.9	3.8	10.3	0.8	11.9	1.4	14.7
HDX07/2.5	80/0.20*	2.0	0.9	3.8	11.4	0.8	13.0	1.4	15.8
HDX03/4.0	127/0.20**	3.0	1.0	5.0	10.8	0.8	12.4	1.4	15.2
HDX04/4.0	127/0.20**	3.0	1.0	5.0	12.1	0.9	13.9	1.4	16.7
HDX05/4.0	127/0.20**	3.0	1.0	5.0	13.5	0.9	15.3	1.6	18.5
HDX03/6.0	190/0.20*	3.5	1.0	5.5	11.8	0.8	13.4	1.6	16.6
HDX04/6.0	190/0.20*	3.5	1.0	5.5	13.3	0.9	15.1	1.6	18.3
HDX05/6.0	190/0.20*	3.5	1.0	5.5	14.9	1.0	16.9	1.6	20.1
HDX03/10	318/0.20*	4.5	1.0	6.5	14.0	0.9	15.8	2.3	20.4
HDX04/10	318/0.20*	4.5	1.0	6.5	15.7	1.0	17.7	2.3	22.3
HDX05/10	318/0.2*	4.5	1.0	6.5	17.6	1.0	19.6	2.3	24.2
HDX03/16	504/0.20*	6.0	1.0	8.0	17.2	1.0	19.2	2.3	23.8
HDX04/16	504/0.20*	6.0	1.0	8.0	19.3	1.1	21.5	2.3	26.1
HDX05/16	504/0.20*	6.0	1.0	8.0	21.6	1.1	23.8	2.3	28.4
HDX03/25	817/0.20*	7.2	1.2	9.6	20.7	1.1	22.9	2.3	27.5
HDX03/35	1120/0.20*	8.4	1.2	10.8	23.3	1.2	25.7	2.3	30.3

* Compliant to AS5000.1

** Compliant to AS3191

CMI Head Office NSW | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | nswsales@cmielectrical.com.au

CMI QLD-Brisbane

(07) 3863 0749
485A Zillmere Road,
Zillmere QLD 4034
southqdsales@cmielectrical.com.au

CMI QLD - Rockhampton

(07) 4921 0978
Shop 3 at 76 Hollingsworth Street,
North Rockhampton Qld 4701
northqdsales@cmielectrical.com.au

CMI VIC

(03) 9532 1233
3 Dissik Street,
Cheltenham VIC 3192
vicsales@cmielectrical.com.au

CMI WA

(08) 9358 1788
36 Division Street,
Welshpool WA 6106
wasaales@cmielectrical.com.au