

MULTIPAIR OVERALL ALUMINIUM FOIL SCREEN

MULTIPAIR CABLES

Use
 Fixed Low Capacitance cables for RS232 and RS422, Instrumentation and Electronic control.

Insulation
 V-90 HT PVC or Polypropylene as indicated.

Sheath
 Standard Grey V75 PVC. Other materials and colours on request.

Screen
 Overall Aluminium/Polyester Laminate with Tinned Copper Drain Wire.

Conductor
 As per Chart B or C, Multipair Cables in the CMI Cable Catalogue.

Colours
 As Indicated - other colours on request. Minimum order quantity of 500m applies.

Pack
 100 or 500 meter reels.

Note
 These cables are not suitable for direct connection to mains supply.

HCK6 SERIES - POLYPROPYLENE INSULATED (Colour code Chart B)



Part Number	Nearest AWG	No. Of Pairs	Cond. No./Dia. mm	Insulation Thickness mm	Nom. Capacitance	Nom. Dia. mm
HCK601	24	1	7/0.20 TC	0.30	50 pF/m	4.10
HCK602	24	2	7/0.20 TC	0.30	50 pF/m	5.7
HCK603	24	3	7/0.20 TC	0.30	50 pF/m	6.4
HCK604	24	4	7/0.20 TC	0.30	50 pF/m	6.7
HCK606	24	6	7/0.20 TC	0.30	50 pF/m	8.9
HCK608	24	8	7/0.20 TC	0.30	50 pF/m	9.5
HCK610	24	10	7/0.20 TC	0.30	50 pF/m	10.2
HCK612	24	12	7/0.20 TC	0.30	50 pF/m	10.7
HCK616	24	16	7/0.20 TC	0.30	50 pF/m	12.5
HCK620	24	20	7/0.20 TC	0.30	50 pF/m	14.0
HCK625	24	25	7/0.20 TC	0.30	50 pF/m	14.7

* Capacitance between conductor pairs.
 TC = Tinned Copper

CMI Head Office NSW | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | nswsales@cmielectrical.com.au
CMI QLD-Brisbane
 (07) 3863 0749
 485A Zillmere Road,
 Zillmere QLD 4034
southqldsales@cmielectrical.com.au

CMI QLD - Rockhampton
 (07) 4921 0978
 Shop 3 at 76 Hollingsworth Street,
 North Rockhampton Qld 4701
northqldsales@cmielectrical.com.au

CMI VIC
 (03) 9532 1233
 3 Dissik Street,
 Cheltenham VIC 3192
vicsales@cmielectrical.com.au

CMI WA
 (08) 9358 1788
 36 Division Street,
 Welshpool WA 6106
walesales@cmielectrical.com.au