

MULTIPAIR INDIVIDUAL AND OVERALL SCREEN

MULTIPAIR CABLES

Use
 Low Capacitance Audio, Control and Computer cable, suitable, RS232, RS422 and RS485.

Insulation
 Polypropylene

Sheath
 Standard Grey V75 PVC. Other materials and colours on request.

Screen
 Each pair has its own Aluminium foil screen and Drain wire together with an overall Aluminium foil screen and Drain wire.

Conductor
 As per Chart B, Multipair Cables in the CMI Cable Catalogue.

Colours
 As indicated - other colours on request. Minimum order quantity of 500m applies.

Pack
 100 or 500 meter reels.

Note
 These cables are not suitable for direct connection to mains supply.

HCK9 SERIES



Part Number	Nearest AWG	No. Of Pairs	Cond. No./Dia. mm	Insulation Thickness mm	Nom. Wire to Wire Capacitance	Nom. Dia. mm
HCK902	24	2	7/0.20 TC	0.30	68 pF/m	6.0
HCK903	24	3	7/0.20 TC	0.30	68 pF/m	7.1
HCK904	24	4	7/0.20 TC	0.30	68 pF/m	7.4
HCK906	24	6	7/0.20 TC	0.30	68 pF/m	9.1
HCK908	24	8	7/0.20 TC	0.30	68 pF/m	9.9
HCK910	24	10	7/0.20 TC	0.30	68 pF/m	11.2
HCK912	24	12	7/0.20 TC	0.30	68 pF/m	12.0
HCK916	24	16	7/0.20 TC	0.30	68 pF/m	13.0
HCK920	24	20	7/0.20 TC	0.30	68 pF/m	14.0
HCK925	24	25	7/0.20 TC	0.30	68 pF/m	15.3

TC = Tinned Copper

CMI Head Office NSW | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | nswsales@cmielectrical.com.au
CMI QLD-Brisbane
 (07) 3863 0749
 485A Zillmere Road,
 Zillmere QLD 4034
southqldsales@cmielectrical.com.au

CMI QLD - Rockhampton
 (07) 4921 0978
 Shop 3 at 76 Hollingsworth Street,
 North Rockhampton Qld 4701
northqldsales@cmielectrical.com.au

CMI VIC
 (03) 9532 1233
 3 Dissik Street,
 Cheltenham VIC 3192
vicsales@cmielectrical.com.au

CMI WA
 (08) 9358 1788
 36 Division Street,
 Welshpool WA 6106
wasales@cmielectrical.com.au