

MULTIPAIR OVERALL ALUMINIUM FOIL AND TINNED COPPER BRAID SCREEN

MULTIPAIR CABLES

Use

Low capacitance RS232, RS422 applications.

Insulation

Polypropylene or Polyethylene as in indicated.

Sheath

Standard Grey V75 PVC. Other materials and colour on request.

Screen

Overall Aluminium/Polyester Laminate and Tinned Copper Wire screens with Stranded Tinned Copper Drain Wire, between the screens.

Colours

As per Section B, Multipair Cables in the CMI Cable Catalogue.

Note

These cables are not suitable for direct connection to mains supply.

K61 SERIES



Part Number	Nearest AWG	No. Of Pairs	Cond. No./Dia. mm	Insulation Thickness mm	Nom. Capacitance	Nom. Dia. mm
K6102	24	2	7/0.20 TC	0.30	50 pF/m	6.1
K6103	24	3	7/0.20 TC	0.30	50 pF/m	7.5
K6104	24	4	7/0.20 TC	0.30	50 pF/m	8.2
K6106	24	6	7/0.20 TC	0.30	50 pF/m	9.0
K6108	24	8	7/0.20 TC	0.30	50 pF/m	10.9
K6110	24	10	7/0.20 TC	0.30	50 pF/m	11.2
K6112	24	12	7/0.20 TC	0.30	50 pF/m	11.3
K6116	24	16	7/0.20 TC	0.30	50 pF/m	13.0
K6120	24	20	7/0.20 TC	0.30	50 pF/m	14.5
K6125	24	25	7/0.20 TC	0.30	50 pF/m	15.2

*Capacitance between conductors of a pair.

TC = Tinned Copper

CMI Head Office NSW | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | nswsales@cmielectrical.com.au

CMI QLD-Brisbane

(07) 3863 0749
 485A Zillmere Road,
 Zillmere QLD 4034
 southqldsales@cmielectrical.com.au

CMI QLD – Rockhampton

(07) 4921 0978
 Shop 3 at 76 Hollingsworth Street,
 North Rockhampton Qld 4701
 northqldsales@cmielectrical.com.au

CMI VIC

(03) 9532 1233
 3 Dissik Street,
 Cheltenham VIC 3192
 vicsales@cmielectrical.com.au

CMI WA

(08) 9358 1788
 36 Division Street,
 Welshpool WA 6106
 wasales@cmielectrical.com.au