

MULTIPAIR EXTRA LOW CAPACITANCE CABLE

MULTIPAIR CABLES

**Use**  
 POS & RS485 applications.

**Insulation**  
 Polyethylene

**Nom. Impedence**  
 120 Ohms

**Cond. Colours**  
 HCY366 Red & Black  
 HCY097 Black & White, Red & Lt. Green  
 HCY315 Black & White, Red & Lt. Green, Blue & Yellow, Orange & Brown

**Compliance**  
 HCY366 is AUSTEL approved.

**Note**  
 These cables are not suitable for direct connection to mains supply. Minimum order quantity will apply for some items.

EXTRA LOW CAPACITANCE CABLE



Part Number	Nearest AWG	No. Of Pairs	Cond. No./Dia. mm	Insulation Thickness mm	Nom. Capacitance	Nom. Dia. mm
HCY366	24	1	7/0.20 TC	0.45	40 pf/m	6.10
HCY097	24	2	7/0.20 TC	0.45	40 pf/m	7.90
HCY315	24	4	7/0.20 TC	0.45	40 pf/m	9.30

\*Capacitance between conductors of a pair.  
 TC = Tinned Copper

**CMI Head Office NSW** | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | [nswsales@cmielectrical.com.au](mailto:nswsales@cmielectrical.com.au)  
**CMI QLD-Brisbane**  
 (07) 3863 0749  
 485A Zillmere Road,  
 Zillmere QLD 4034  
[southqldsales@cmielectrical.com.au](mailto:southqldsales@cmielectrical.com.au)

**CMI QLD - Rockhampton**  
 (07) 4921 0978  
 Shop 3 at 76 Hollingsworth Street,  
 North Rockhampton Qld 4701  
[northqldsales@cmielectrical.com.au](mailto:northqldsales@cmielectrical.com.au)

**CMI VIC**  
 (03) 9532 1233  
 3 Dissik Street,  
 Cheltenham VIC 3192  
[vicsales@cmielectrical.com.au](mailto:vicsales@cmielectrical.com.au)

**CMI WA**  
 (08) 9358 1788  
 36 Division Street,  
 Welshpool WA 6106  
[wasales@cmielectrical.com.au](mailto:wasales@cmielectrical.com.au)