

MULTIPAIR EXTRA LOW CAPACITANCE CABLE

MULTIPAIR CABLES

Use
 POS & RS485 applications.

Insulation
 Polyethylene

Nom. Impedence
 120 Ohms

Cond. Colours
 HCY366 Red & Black
 HCY097 Black & White, Red & Lt. Green
 HCY315 Black & White, Red & Lt. Green, Blue & Yellow, Orange & Brown

Compliance
 HCY366 is AUSTEL approved.

Note
 These cables are not suitable for direct connection to mains supply. Minimum order quantity will apply for some items.

EXTRA LOW CAPACITANCE CABLE



Part Number	Nearest AWG	No. Of Pairs	Cond. No./Dia. mm	Insulation Thickness mm	Nom. Capacitance	Nom. Dia. mm
HCY366	24	1	7/0.20 TC	0.45	40 pf/m	6.10
HCY097	24	2	7/0.20 TC	0.45	40 pf/m	7.90
HCY315	24	4	7/0.20 TC	0.45	40 pf/m	9.30

*Capacitance between conductors of a pair.
 TC = Tinned Copper

CMI Head Office NSW | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | nswsales@cmielectrical.com.au
CMI QLD-Brisbane
 (07) 3863 0749
 485A Zillmere Road,
 Zillmere QLD 4034
southqldsales@cmielectrical.com.au

CMI QLD - Rockhampton
 (07) 4921 0978
 Shop 3 at 76 Hollingsworth Street,
 North Rockhampton Qld 4701
northqldsales@cmielectrical.com.au

CMI VIC
 (03) 9532 1233
 3 Dissik Street,
 Cheltenham VIC 3192
vicsales@cmielectrical.com.au

CMI WA
 (08) 9358 1788
 36 Division Street,
 Welshpool WA 6106
wasales@cmielectrical.com.au