

4 CORE INSTALLATION SPEAKER CABLE

HOME AUTOMATION CABLES

**Use**  
 Ideal for permanent installations of Audio and Home Theatre Systems

**Conductor**  
 Stranded Bare Copper Wires

**Insulation**  
 PVC (V90, RoHS)

**Sheath**  
 PVC (V75, RoHS) White. Other colours on request.

**Core Colour**  
 Red, Black, Green & White.

**Flame Retardance**  
 VW-1

**Pack**  
 100 or 500 meter reels.

**Dielectric Strength Test**  
 2.0kV(AC) / 1 min. Min.

INSTALLATION SPEAKER CABLE



Conductor

Cable

Part Number	Nearest AWG	No. Of Cores	Cond. No./Dia. mm	Insulation Thickness mm	Insulation Outer Dia.	Nom. Sheath Thickness mm	Sheath Dia.	Conductor resistance @20°C Ω/km
HGX103	18	4	12/0.30 BC	0.55	2.30	1.00	7.60	21.4

**CMI Head Office NSW** | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | [nswsales@cmielectrical.com.au](mailto:nswsales@cmielectrical.com.au)

**CMI QLD-Brisbane**  
 (07) 3863 0749  
 485A Zillmere Road,  
 Zillmere QLD 4034  
[southqldsales@cmielectrical.com.au](mailto:southqldsales@cmielectrical.com.au)

**CMI QLD - Rockhampton**  
 (07) 4921 0978  
 Shop 3 at 76 Hollingsworth Street,  
 North Rockhampton Qld 4701  
[northqldsales@cmielectrical.com.au](mailto:northqldsales@cmielectrical.com.au)

**CMI VIC**  
 (03) 9532 1233  
 3 Dissik Street,  
 Cheltenham VIC 3192  
[vicsales@cmielectrical.com.au](mailto:vicsales@cmielectrical.com.au)

**CMI WA**  
 (08) 9358 1788  
 36 Division Street,  
 Welshpool WA 6106  
[wasaes@cmielectrical.com.au](mailto:wasaes@cmielectrical.com.au)