

4 CORE INSTALLATION SPEAKER CABLE

HOME AUTOMATION CABLES

Use
 Ideal for permanent installations of Audio and Home Theatre Systems

Conductor
 Stranded Bare Copper Wires

Insulation
 PVC (V90, RoHS)

Sheath
 PVC (V75, RoHS) White. Other colours on request.

Core Colour
 Red, Black, Green & White.

Flame Retardance
 VW-1

Pack
 100 or 500 meter reels.

Dielectric Strength Test
 2.0kV(AC) / 1 min. Min.

INSTALLATION SPEAKER CABLE



Conductor

Cable

Part Number	Nearest AWG	No. Of Cores	Cond. No./Dia. mm	Insulation Thickness mm	Insulation Outer Dia.	Nom. Sheath Thickness mm	Sheath Dia.	Conductor resistance @20°C Ω/km
HGX103	18	4	12/0.30 BC	0.55	2.30	1.00	7.60	21.4

CMI Head Office NSW | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | nswsales@cmielectrical.com.au

CMI QLD-Brisbane
 (07) 3863 0749
 485A Zillmere Road,
 Zillmere QLD 4034
southqldsales@cmielectrical.com.au

CMI QLD - Rockhampton
 (07) 4921 0978
 Shop 3 at 76 Hollingsworth Street,
 North Rockhampton Qld 4701
northqldsales@cmielectrical.com.au

CMI VIC
 (03) 9532 1233
 3 Dissik Street,
 Cheltenham VIC 3192
vicsales@cmielectrical.com.au

CMI WA
 (08) 9358 1788
 36 Division Street,
 Welshpool WA 6106
wasaes@cmielectrical.com.au