

COMPOSITE POWER & COAX CABLE

HOME AUTOMATION CABLES

Use

Permanent Installation of Security Cameras & Systems where Power and Video is required.

Shield Braid

16/7/0.16mm, Bare Copper Wires, with 95% coverage minimum.

Inner Sheath

Black PVC, 0.9mm Nominal Thickness, 6.3mm (+/- 0.15) Outer Diameter.

Assembly

3 cores are cabled together.

Ripcord

Nylon Rope

Outer Sheath

Black PVC, 0.8mm Nominal thickness, 10.70mm (+/- 0.20) Outer Diameter.

COMPOSITE POWER & COAX



Part Number	No. Of Cores	Nom. Sizes	Insulation Material	Nom. Insulation Thickness mm	Nom. Insulation Dia. mm	Insulation Colour
HCY713	1 x (RG59/U)	23 AWG (1/0.60)	LDPE	1.58	3.75 (+/-0.10)	Natural
	2 x 0.75mm ²	24/0.20	PVC	0.85	2.80 (+/-0.10)	Red, Black

CMI Head Office NSW | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | nswsales@cmielectrical.com.au
CMI QLD-Brisbane
 (07) 3863 0749
 485A Zillmere Road,
 Zillmere QLD 4034
southqldsales@cmielectrical.com.au

CMI QLD - Rockhampton
 (07) 4921 0978
 Shop 3 at 76 Hollingsworth Street,
 North Rockhampton Qld 4701
northqldsales@cmielectrical.com.au

CMI VIC
 (03) 9532 1233
 3 Dissik Street,
 Cheltenham VIC 3192
vic-sales@cmielectrical.com.au

CMI WA
 (08) 9358 1788
 36 Division Street,
 Welshpool WA 6106
wasa-sales@cmielectrical.com.au