

COMPOSITE POWER & COAX CABLE

HOME AUTOMATION CABLES

**Use**  
 Permanent Installation of Security Cameras & Systems where Power and Video is required.

**Shield Braid**  
 16/7/0.16mm, Bare Copper Wires, with 95% coverage minimum.

**Inner Sheath**  
 Black PVC, 0.9mm Nominal Thickness, 6.3mm (+/- 0.15) Outer Diameter.

**Assembly**  
 3 cores are cabled together.

**Ripcord**  
 Nylon Rope

**Outer Sheath**  
 Black PVC, 0.8mm Nominal thickness, 10.70mm (+/- 0.20) Outer Diameter.

COMPOSITE POWER & COAX



Part Number	No. Of Cores	Nom. Sizes	Insulation Material	Nom. Insulation Thickness mm	Nom. Insulation Dia. mm	Insulation Colour
HCY713	1 x (RG59/U)	23 AWG (1/0.60)	LDPE	1.58	3.75 (+/-0.10)	Natural
	2 x 0.75mm <sup>2</sup>	24/0.20	PVC	0.85	2.80 (+/-0.10)	Red, Black

**CMI Head Office NSW** | (02) 9807 6155 | F3, 3-29 Birnie Ave, Lidcombe, NSW, 2141 | [nswsales@cmielectrical.com.au](mailto:nswsales@cmielectrical.com.au)  
**CMI QLD-Brisbane**  
 (07) 3863 0749  
 485A Zillmere Road,  
 Zillmere QLD 4034  
[southqldsales@cmielectrical.com.au](mailto:southqldsales@cmielectrical.com.au)

**CMI QLD - Rockhampton**  
 (07) 4921 0978  
 Shop 3 at 76 Hollingsworth Street,  
 North Rockhampton Qld 4701  
[northqldsales@cmielectrical.com.au](mailto:northqldsales@cmielectrical.com.au)

**CMI VIC**  
 (03) 9532 1233  
 3 Dissik Street,  
 Cheltenham VIC 3192  
[vic-sales@cmielectrical.com.au](mailto:vic-sales@cmielectrical.com.au)

**CMI WA**  
 (08) 9358 1788  
 36 Division Street,  
 Welshpool WA 6106  
[wasa-sales@cmielectrical.com.au](mailto:wasa-sales@cmielectrical.com.au)